



Type CRBCA

Belt Drive Centrifugal Power Roof Ventilators



AMERICAN COOLAIR CORPORATION

P.O. Box 2300 Jacksonville, Florida 32203
 Phone: (904) 389-3646
 Fax: (904) 387-3449 • (904) 381-7560
 E-mail: fans@coolair.com
 Internet: www.coolair.com



Standard Fan Features

- Non-overloading aluminum wheel with "C-Drive" computer balanced.
- Force ventilated motor compartment isolated from airstream.
- Variable pitch motor pulley.
- Vibration isolators on drive frame.
- Weatherproof spun aluminum housing.
- NEMA Standard frame size motors.
- Overlapping wheel/inlet venturi.
- "C-Drive" engineered to provide 1,000,000 hours L10 bearing life.
- AMCA label for air and sound.
- Galvanized mesh birdscreen.

Optional Features

- UL Label for Standard 705.
- Disconnect switch (loose or factory mounted and wired).
- Backdraft damper.
- Roof curb (damper shelf optional).
- Epoxy coating.

Unit Size	Ventilator Dimensions			Roof Curb and Damper Dimensions				
	A	B	C	D	E	G	H	J
06-10	18	23 1/8	20 1/2	24 1/2	12 3/4	11 1/4	16 1/2	13 1/4
12-15	23	28 5/8	22 1/2	29 1/2	17 3/4	16 1/4	21 1/2	18 1/4
16-20	30	35 1/2	24 5/8	36 1/2	24 3/4	23 1/4	28 1/2	25 1/4
24	34	42 3/4	32 1/2	40 1/2	28 3/4	27 1/4	32 1/2	29 1/4

Check here for UL 705.

Dimensions In Inches

Specifications

FAN NO.	QTY.	FAN DATA					MOTOR DATA						ACCESSORIES AND REMARKS
		MODEL NO.	CFM	SP	RPM	SONES	HP	RPM	VOLTAGE	PH	HZ	ENCLOSURE	

PROJECT _____ ENGINEER _____ SUBMITTED BY _____ DATE _____

LOCATION _____ CONTRACTOR _____ APPROVED BY _____ DATE _____